## Approved For Release 2002/07/10 : CIA-RDP69B00041R001800010032-4

25X1A ,,,,,≥,	à tạt		⊒impo impo	<b>1</b>		ROUTINE	25X1
	11 4 1	ີ 25X1A		25	X1A		A CANADA
	FREE						
			teat and and a security		1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		
	1	EVALUATION	TEPUFI			**************************************	
O.	TYPE	17073884					
ø.	FULT	ron ses/ <b>nxaj</b>	IN/47" SEC/	HT DEGREE	is F./Has	R 1µ40→ BAF 1	• ¥ ₩
E	1.60	/2.51					
V.	1.40年	/2154/485-4-	-3-11-7				
4.	x # )	¢000					
	+2)	TO MAL					
	(3)	MED I UP					Page 1
		6.000					****
	£ 44 7						
	£33.	OPERATIONAL	• • • • • • • • • • • • • • • • • • • •			2 de 1	
	(6)	HORMAL					
	7.73	95 PEFCENT	erom con	R NORTH	/1E" Ha /	D PERCENT CL	OUD CEVER
5X1A		OVERALL MIS	. #108	*Style   Style   Style   Style			
». ₩.	() . W	DISPOSITION	70				
	i Du	PE POS 10 M	ATIONAL CU	TONEAS			
	The same of	PE POS 2 DIJ			PER COLUMN D		

25X1A
PAGE 2 0.73 T L P S E C 7 E T

EVERY OTHER PRAMES APPROX 1/8" INTO PRAME. BACK ABBRASSIONS S"

IN PROM TRAILING EDGE FROM BIS TO ND OF MISSION. PECYCLYING PROM

556 THROUGH 973. PRESSURE MARKS ON BASE SIDE. STREAKS WERE NOTED ON

FRAME OF RAND AND AT INCHES IN FROM LEADING EDGE. HINUS DENSITY.

STREAKS IN FORWARD FRAMES NOTICEBLE ONLY IN HORIZON ON FORWARD

FRAME. PLUS DENSITY STREAKS WERE APPARENT IN HORIZON ON FORWARD

FRAMES RUNNING FROM LEADING TO TRAILING EDGE. FACTORY SPLACE IN

FRAME 1182. PINHOLE IN BAL 1/2" IN 1 3/4" FROM TITLING SIDE. HART 12

FAD SUMMEROUS MANDLING SCRATCHES THROUGHOUT. FRAME 842. 1856, 1252.

1291 HAD NUMEROUS HANDLING SCRATCHES. 1386-1389 2 SCRATCHES 3

INCHES IN 1/4" APART. FRAMES 721-725 WERE GREELAPED. 731, 734

PAD 9 STREAKS RUNNING VERTICAL. FRAMES 1384-1318 WERE FOG.

. .

Dom